PIG SpillBlocker Containment Dikes

Instructions

- 1. Clean surface where you will place the dike to ensure a tight seal. (Debris can reduce the quality of the seal.)
- 2. Place the dike with widest side down.
- 3. Care should be taken when removing the dike from applied surface, to avoid tearing.
- 4. When finished, wash the dike using warm water and a nonabrasive detergent.
- 5. Dry the dike with a clean towel, cloth, or wiper (or allow to air dry on a rack) before storing.
- 6. Store the dike in its original package and out of direct sunlight.
- 7. If the dike was originally wrapped in a poly sheet, save and reuse it for storage.

PLEASE NOTE: Some chemicals will degrade this product. Refer to our online chemical resistance guide for information.

Care & Storage of Urethane Products

- As with all urethane products, please inspect regularly to ensure it is in a usable state
- The containment dike performs best when used on a smooth surface
- Prevent the dike from touching itself for long periods of time (it could possibly stick enough to cause damage to product)
- If this product is used in a spill response effort involving incompatible liquids, it should be disposed of with other spill response materials
- Do not store in high humidity, or where temperatures exceed 120°F
- The flexibility and sealing functions diminish at temperatures below -30°F

NOTE:

Due to the nature of softer urethane, the physical properties of these products may change over time with exposure to certain environmental conditions like temperature, humidity and UV radiation. Typical product life expectancy is 5 years. Please inspect the stored product regularly to ensure it is in a usable state. See newpig.com for chemical compatibility and urethane care guidelines.



PLR213 - Quickly seal off a doorway from a spreading spill or washdown liquid.



PLR204 - Confine liquids at the source of a spill for easy cleanup with absorbents.



North America: **1-800-468-4647** Europe: **+31 (0)76 596 92 50** UK: 0800 919 900

Outside North America: +1-814-684-0101